



Glass Thickness	Spacer	OD	U-Value Btu/h-ft ² -F ²	U-Value W/m ² -K ²	SHGC	CR	ER	CND Energy Star Zone	USA Energy Star Zone
-----------------	--------	----	--	---	------	----	----	----------------------	----------------------

690 MC/WD Hinge French Door (Inswing)

SOL-R®-I 270 / Clear

3/3mm	XL Edge SS	0.875	0.31	1.76	0.24	63	15	A, B	N, NC,SC,S
4/4mm	XL Edge SS	0.875	0.31	1.76	0.23	62	15	A, B	N, NC,SC,S

690 MC/WD Hinge French Door (Outswing)

SOL-R®-I 178 / Clear

3/3mm	XL Edge SS	0.875	0.33	1.87	0.39	58	21	A, B	N, NC,SC,S
-------	------------	-------	------	------	------	----	----	------	------------

SOL-R®-I 270 / Clear

3/3mm	XL Edge SS	0.875	0.30	1.70	0.24	63	17	A, B	N, NC,SC,S
4/4mm	XL Edge SS	0.875	0.30	1.70	0.23	62	16	A, B	N, NC,SC,S

Legend: + USA Energy Star Designations: "N" = Northern, "NC" = North/Central, "SC" South/Central, "S" = Southern
 + Standards: U-values = NFRC100-01; SHGC/VT = NFRC 200-01; CR = NFRC 500-01; ER = CAN/CSA A440.02-04
 + SHGC = Solar Heat Gain Coefficient